

0703

# Automatic Watertight Coupling, 1/2"



1/2" automatic watertight coupling with water stop when disconnected from quick coupling.

# Technical Data

Item Number	0703
Couplings Size	1/2 "
Material	Chromium-plated brass
Suitable for Food Contact (EU 1935/2004), DoC <sup>1</sup>	No
Use of Phthalates (e.g. Bisphenol A)	No
Is Halal compliant	Yes
Box Quantity	1 Pcs.
Quantity per Pallet (80 x 120 x 200 cm)	3180 Pcs
Box Length	335 mm
Box Width	180 mm
Box Height	85 mm
Length	160 mm
Width	67 mm
Height	40 mm
Gross Weight	0,17 kg
Net Weight	0,158 kg
Cubik metre	0,000429 M3
Max. cleaning temperature (Dishwasher)	80 °C
Max usage temperature (food contact)	40 °C
Max usage temperature (non food contact)	70 °C
Min. usage temperature	-30 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Max. bars pressure	25 Bar
Recycling Mark 7	No
Gtin-13 Number	5705020007033
GTIN-14 Number (Box quantity)	15705020007030
Commodity Code	74032100
Country of origin	Denmark

The hose coupling on the hose and foaming gun have to be greased regularly to maintain the coupling ability on the equipment. The grease applied during mounting will be rinsed away by the water flow and thus needs to be renewed.