

Declaration of Compliance

Business Operator	Vikan A/S Rævevej 1 DK-7800 Skive (+45) 96 14 26 00
Description	Powder Brush, 300 mm, Soft, Green
Item Number	45822
Plastic Material	Polypropylene, 97 %
Colour masterbatch	Green, 2 %
Foaming agent	Chemical foaming agent, 1 %
Bristles	Polybutylene terephthalate (PBT)
Stainless steel	The stainless steel thread is made from stainless steel Grade 1.4301 (AISI 304)
EU Compliance	
US FDA Compliance	
Migration analysis plastics	Samples of the product, or a similar product made from identical plastic material, have been tested for overall migration according to the test conditions specified in (EU) 10/2011, and the article comply with the overall migration limit of 10 mg/dm ² or 60 mg/kg.
	Test conditions for overall migration were OM2 (10 days at 40 °C)
	Test conditions for overall migration were OM2 (10 days at 40 °C) Food simulants used for overall migration were 50 % ethanol (simulant D1), 3 % acetic acid (simulant B) and olive oil (simulant D2)
	Food simulants used for overall migration were 50 % ethanol (simulant D1), 3 % acetic
Food contact types	Food simulants used for overall migration were 50 % ethanol (simulant D1), 3 % acetic acid (simulant B) and olive oil (simulant D2) Compliance with specific migration limits, and other restrictions, has been documented
Food contact types	Food simulants used for overall migration were 50 % ethanol (simulant D1), 3 % acetic acid (simulant B) and olive oil (simulant D2)Compliance with specific migration limits, and other restrictions, has been documented through testing, calculation or simulation.The product is suitable for contact with the following types of food under the intended and
Food contact types	Food simulants used for overall migration were 50 % ethanol (simulant D1), 3 % acetic acid (simulant B) and olive oil (simulant D2)Compliance with specific migration limits, and other restrictions, has been documented through testing, calculation or simulation.The product is suitable for contact with the following types of food under the intended and foreseeable conditions of use:
Food contact types	 Food simulants used for overall migration were 50 % ethanol (simulant D1), 3 % acetic acid (simulant B) and olive oil (simulant D2) Compliance with specific migration limits, and other restrictions, has been documented through testing, calculation or simulation. The product is suitable for contact with the following types of food under the intended and foreseeable conditions of use: Aqueous Acidic Alcoholic
Food contact types	 Food simulants used for overall migration were 50 % ethanol (simulant D1), 3 % acetic acid (simulant B) and olive oil (simulant D2) Compliance with specific migration limits, and other restrictions, has been documented through testing, calculation or simulation. The product is suitable for contact with the following types of food under the intended and foreseeable conditions of use: Aqueous Acidic



\checkmark	Dry
--------------	-----

Food contact usage time and temperature	Any long term storage at room temperature or below, including heating up to 70 °C for up to 2 hours, or heating up to 100 °C for up to 15 minutes.
Non-food contact usage temperature	Minimum temperature: -20 °C Maximum temperature: 100 °C
General	Equipment should be cleaned, disinfected and sterilised, as appropriate to it's intended use, before use.
	It is also important to clean, disinfect and sterilise equipment as appropriate after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.
	Appropriate equipment decontamination will minimise the risk of microbial growth and cross contamination and will maximise the efficiency and durability of the equipment.
	Max. Wash temp.: 121 °C
	We will make the relevant background documentation available to the competent authorities, at their request.
	Vikan A/S is registered with the Danish Veterinary and Food Administration (DVFA), and our mandatory Own Control System is subject to inspection by the DVFA.

Date

Made By

10/12/2017

Stine Lønnerup Bislev Hygiene and Compliance Manager